

# Welcome to Little Lemonade

## **Towing**

Please make sure before towing that all items inside the RV are secured from movement and placed in their proper place. The fridge does have a strap to keep it from falling out of its location.

1. Make sure that the stabilizer jacks are stowed in their travel stage.
2. Stow and unhook all utilities and awning
3. Using the front tongue jack raises or lower the trailer to attach to tow vehicle.
4. Lower trailer on to hitch.
5. Latch the ball and attach safety chains and emergency brake away cable to vehicle.
6. Raise tongue jack all the way up to its highest point.
7. Plug in trailer lights to vehicle and turn battery disconnect to the on position.

## **Set up & Tare Down**

1. Before disconnecting from vehicle, level the trailer axle from side to side.
2. Once trailer is level (left to right) chock wheels and unhook the tow vehicle.
3. Using the tongue jack level the trailer from nose to tail.
4. Once trailer is fully level lower the stabilizer jacks starting with the back two then the front two.

Notice: stabilizer jacks are not to be used to level the trailer, they are designed to help with the bounciness of the trailer. Lower till they just hit the ground then add a little pressure.

5. hook up power wire and other available utilities.
  1. Please use the surge protector for power (Never use without)
  2. please use the pressure regulator for water (never use without)
6. pull out step.
7. Extend the slide out. Make sure that there is enough room outside the trailer for the slide to extend. On the inside make sure there is nothing on the floor or cabinet doors closed on each side of the slide to prevent any damage when in operation. DO NOT extend slide without leveling trailer, failure to do so may cause damage.

For tare down follow steps above in reverse order.

## **Stove top**

Make sure the gas (propane tank) is on.

Use a match or lighter to light cook top

Make sure the vent is open when cooking in the RV

## **Power / Electrical**

This unit is has a 30amp plug. Which should always be the best to plug into to utilize all the amenities that the RV has to offer.

You are capable of plugging in to a 20amp outlet (standard house outlet) but are limited to some items in the camper. For example, you can run the A/C but not the microwave.

Plugging in to shore power.

1. attach power wire to trailer
2. attach surge protector to power wire
  1. There is an attachment for 20amp (house hold outlet) this would go between the surge protector and the power source.
3. attach surge protector to power source.
4. Turn battery disconnect off

to unhook power please follow the steps in reverse order

## **Water**

There are two options when it comes to water

1. Water Tank (20 gal) for use when not hooked to city water.
  1. turn water pump on at control panel.
  2. Do not leave "on" when not in use
2. City Water
  1. attach 90 degree to RV City Water connection
  2. attach hose to 90 degree attachment
  3. attach pressure regulator to other end of hose
  4. attach pressure regulator to water source.
  5. Turn :on: water source.

To disconnect water follow steps above in reverse order.

## Hot water tank

This unit comes with a 10gal gas hot water tank

When not connected to City Water please turn water pump “on” for the duration the water heater is on. Failure to do so will result in injury or damage.

1. Make sure the gas (Propane tank) is on
2. turn on switch under control panel cabinet.
3. Allow 20 min to heat water in tank.
4. Once the need for hot water is gone please turn “off” hot water switch

If you wish, you can keep the hot water heater on while you are camping, however, this will use some propane while you are camping. The water tank will turn on and off to maintain temperature. We would advise only using the hot water heater when you need to.

## Septic / Tanks

There are two tanks for dirty water

1. Gray tank – shower and sink water
2. Black tank – toilet water

### Sewer Connections

1. remove hose from bumper
2. attach hose to camper
3. attach 90 degree coupling to other end of hose
4. attach coupling to sites sewer

It is advised not to open the valves during your stay until the tanks are full or when it is time to leave the site. DO NOT leave tank valves open when camping. Holding tanks are designed to be used like a port-a-potty. Use it till you fill it then dump it. This keep the sewer smell from traveling into the camper from the campground.

### Dumping the tanks

1. Black tank
2. Gray tank

Always dump the black tank first so that the gray tank cleans the sewer hose from any obstructions from the black tank.

If you are connected to water but do not have a sewer connection, be aware that you will have more water than tanks space to store water.

## **Awning**

The awning is powered by both the battery and shore power.

Just press the awning button on the RV's Control panel to operate.

Strong Wind – please do not use in strong winds. Failure to do so this could damage the awning and awning system

Rain – please remember to slant the awning to allow water to drain off to one side. Failure to do this may cause damage to awning and awning system.

## **Lights**

All lights in the unit are manually operated. To turn on and off press the center button on the light you would like on. Lights are also powered by both shore power and battery.

## **A/C Unit**

This unit is equipped with a ceiling mounted A/C unit. This is very simple to operate given the controls on the unit itself.

If the unit does not turn on check the plug, may need reset.

## **Heat / Fire place**

This unit comes with forced air gas heat. Simply set the desired temperature and make sure the propane tank is on. The system will turn itself on and off to maintain temperature.

## **TV**

The unit does have a tv antenna built in. If you have a tv and want to connect it to local tv, simply connect the cable to the tv cable jack inside the unit. The antenna will automatically tune itself to the direction of the closest tower. Then run a channel search program on your tv and your all set.